



FESTO T-Fitting NPFC

Characteristics

Series: NPFC

Ambient temperature: -20 / 150 °C

Operating pressure: -0.95 / 50 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size in	Threaded connection 2	Connection 2 thread size in	Article
NPFC-T-2R18-G18-MMF	Brass, Nickel-plated	External thread BSPT (R)	1/8	Internal thread BSPP (G)	1/8	NPFC-T-2R18-G18-MMF
NPFC-T-R18-2G18-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/8	Internal thread BSPP (G)	1/8	NPFC-T-R18-2G18-MFF
NPFC-T-3R14-M	Brass, Nickel-plated	External thread BSPT (R)	1/4			NPFC-T-3R14-M
NPFC-T-2R14-G14-MMF	Brass, Nickel-plated	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/4	NPFC-T-2R14-G14-MMF
NPFC-T-R14-2G14-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/4	NPFC-T-R14-2G14-MFF
NPFC-T-3R38-M	Brass, Nickel-plated	External thread BSPT (R)	3/8			NPFC-T-3R38-M
NPFC-T-R38-2G38-MFF	Brass, Nickel-plated	External thread BSPT (R)	3/8	Internal thread BSPP (G)	3/8	NPFC-T-R38-2G38-MFF
NPFC-T-3R12-M	Brass, Nickel-plated	External thread BSPT (R)	1/2			NPFC-T-3R12-M
NPFC-T-2R12-G12-MMF	Brass, Nickel-plated	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/2	NPFC-T-2R12-G12-MMF
NPFC-T-R12-2G12-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/2	NPFC-T-R12-2G12-MFF
NPFC-T-3M5-FMF	Brass, Nickel-plated	Internal thread (M)	M 5	External thread (M)	M 5	NPFC-T-3M5-FMF
NPFC-T-3G18-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/8			NPFC-T-3G18-F
NPFC-T-2G18-R18-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1/8	External thread BSPT (R)	1/8	NPFC-T-2G18-R18-FMF
NPFC-T-3G14-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/4			NPFC-T-3G14-F
NPFC-T-G14-2R14-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	External thread BSPT (R)	1/4	NPFC-T-G14-2R14-FMM
NPFC-T-2G14-R14-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	External thread BSPT (R)	1/4	NPFC-T-2G14-R14-FMF
NPFC-T-3G38-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/8			NPFC-T-3G38-F
NPFC-T-2G38-R38-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	External thread BSPT (R)	3/8	NPFC-T-2G38-R38-FMF
NPFC-T-G38-2R38-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	External thread BSPT (R)	3/8	NPFC-T-G38-2R38-FMM
NPFC-T-3G12-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/2			NPFC-T-3G12-F
NPFC-T-G12-2R12-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	External thread BSPT (R)	1/2	NPFC-T-G12-2R12-FMM
NPFC-T-2G12-R12-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	External thread BSPT (R)	1/2	NPFC-T-2G12-R12-FMF
NPFC-T-3G34-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/4			NPFC-T-3G34-F
NPFC-T-2G34-R34-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	3/4	External thread BSPT (R)	3/4	NPFC-T-2G34-R34-FMF
NPFC-T-3G1-F	Brass, Nickel-plated	Internal thread BSPP (G)	1			NPFC-T-3G1-F
NPFC-T-2G1-R1-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1	External thread BSPT (R)	1	NPFC-T-2G1-R1-FMF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.