



FESTO Suction cup VAS

Characteristics

Series: VAS

Suction cup shape: Round flat

Connection position: Top

Material	Diameter mm	Nominal size mm	Colour	Connection	Type of fastening	Operating pressure bar	Nominal pressure bar	Shore hardness	Weight g	Article
NBR	2	1	Black	M 3				55 +/- 5	0	VAS-2-M3-NBR
NBR	5	1.5	Black	M 5				55 +/- 5	0	VAS-5-M5-NBR
NBR	8	2	Black	M 5				60 +/- 5	0	VAS-8-M5-NBR
NBR	10	2	Black	M 5				60 +/- 5	0	VAS-10-M5-NBR
NBR	15	3	Black	G1/8				60 +/- 5	0	VAS-15-1/8-NBR
NBR	30	3	Black	G1/8				70 +/- 5	0	VAS-30-1/8-NBR
NBR	40	4	Black	G1/4				70 +/- 5	0	VAS-40-1/4-NBR
NBR	55	4	Black	G1/4				70 +/- 5	0	VAS-55-1/4-NBR
NBR	75	4	Black	G1/4				70 +/- 5	0	VAS-75-1/4-NBR
NBR	100	4	Black	G1/4				70 +/- 5	0	VAS-100-1/4-NBR
NBR	125	7	Black	G3/8				70 +/- 5	0	VAS-125-3/8-NBR
PUR	8	2	Blue	M 5	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	4	VAS-8-M5-PUR-B
PUR	10	2	Blue	M 5	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	4	VAS-10-M5-PUR-B
PUR	15	3	Blue	G1/8	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	11	VAS-15-1/8-PUR-B
PUR	30	3	Blue	G1/8	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	12	VAS-30-1/8-PUR-B
PUR	40	4	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	26	VAS-40-1/4-PUR-B
PUR	55	4	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	30	VAS-55-1/4-PUR-B
PUR	75	4	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	77	VAS-75-1/4-PUR-B
PUR	100	4	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	140	VAS-100-1/4-PUR-B
PUR	125	7	Blue	G3/8	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	249	VAS-125-3/8-PUR-B
VMQ/Silicone	8	2	Transparent	M 5	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	2	VAS-8-M5-SI-B
VMQ/Silicone	10	2	Transparent	M 5	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	2	VAS-10-M5-SI-B
VMQ/Silicone	15	3	Transparent	G1/8	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	4	VAS-15-1/8-SI-B
VMQ/Silicone	30	3	Transparent	G1/8	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	5	VAS-30-1/8-SI-B
VMQ/Silicone	40	4	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	14	VAS-40-1/4-SI-B
VMQ/Silicone	55	4	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	19	VAS-55-1/4-SI-B
VMQ/Silicone	75	4	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	62	VAS-75-1/4-SI-B
VMQ/Silicone	100	4	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	116	VAS-100-1/4-SI-B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Material	Diameter mm	Nominal size mm	Colour	Connection	Type of fastening	Operating pressure bar	Nominal pressure bar	Shore hardness	Weight g	Article
VMQ/Silicone	125	7	Transparent	G3/8	Via vacuum port	-0.95 / 0	-0.7	60 +/- 5	214	VAS-125-3/8- SI-B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.