



FESTO Suction cup VASB

Characteristics

Series: VASB

Connection position: Top

Shore hardness: 60 +/- 5

Material	Diameter mm	Nominal size mm	Suction cup shape	Colour	Connection	Type of fastening	Operating pressure bar	Nominal pressure bar	Weight g	Article
NBR	8	2	Round, bellows 1.5 convolutions	Black	M 5				0	VASB-8-M5-NBR
NBR	15	3	Round, bellows 1.5 convolutions	Black	G1/8				0	VASB-15-1/8-NBR
NBR	30	3	Round, bellows 1.5 convolutions	Black	G1/8				0	VASB-30-1/8-NBR
NBR	40	4	Round, bellows 1.5 convolutions	Black	G1/4				0	VASB-40-1/4-NBR
NBR	55	4	Round, bellows 1.5 convolutions	Black	G1/4				0	VASB-55-1/4-NBR
NBR	75	4	Round, bellows 1.5 convolutions	Black	G1/4				0	VASB-75-1/4-NBR
NBR	100	4	Round, bellows 1.5 convolutions	Black	G1/4				0	VASB-100-1/4-NBR
NBR	125	7	Round, bellows 1.5 convolutions	Black	G3/8				0	VASB-125-3/8-NBR
PUR	8	2	Round, bellows 1.5 convolutions	Blue	M 5	Via vacuum port	-0.95 / 0	-0.7	4	VASB-8-M5-PUR-B
PUR	15	3	Round, bellows 1.5 convolutions	Blue	G1/8	Via vacuum port	-0.95 / 0	-0.7	11	VASB-15-1/8-PUR-B
PUR	30	3	Round, bellows 1.5 convolutions	Blue	G1/8	Via vacuum port	-0.95 / 0	-0.7	14	VASB-30-1/8-PUR-B
PUR	40	4	Round, bellows 1.5 convolutions	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	30	VASB-40-1/4-PUR-B
PUR	55	4	Round, bellows 1.5 convolutions	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	39	VASB-55-1/4-PUR-B
PUR	75	4	Round, bellows 1.5 convolutions	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	90	VASB-75-1/4-PUR-B
PUR	100	4	Round, bellows 1.5 convolutions	Blue	G1/4	Via vacuum port	-0.95 / 0	-0.7	155	VASB-100-1/4-PUR-B
PUR	125	7	Round, bellows 1.5 convolutions	Blue	G3/8	Via vacuum port	-0.95 / 0	-0.7	294	VASB-125-3/8-PUR-B
VMQ/Silicone	8	2	Round, bellows 1.5 convolutions	Transparent	M 5	Via vacuum port	-0.95 / 0	-0.7	4	VASB-8-M5-SI-B
VMQ/Silicone	15	3	Round, bellows 1.5 convolutions	Transparent	G1/8	Via vacuum port	-0.95 / 0	-0.7	4	VASB-15-1/8-SI-B
VMQ/Silicone	30	3	Round, bellows 1.5 convolutions	Transparent	G1/8	Via vacuum port	-0.95 / 0	-0.7	7	VASB-30-1/8-SI-B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Material	Diameter mm	Nominal size mm	Suction cup shape	Colour	Connection	Type of fastening	Operating pressure bar	Nominal pressure bar	Weight g	Article
VMQ/Silicone	40	4	Round, bellows 1.5 convolutions	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	18	VASB-40-1/4- SI-B
VMQ/Silicone	55	4	Round, bellows 1.5 convolutions	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	29	VASB-55-1/4- SI-B
VMQ/Silicone	100	4	Round, bellows 1.5 convolutions	Transparent	G1/4	Via vacuum port	-0.95 / 0	-0.7	132	VASB-100-1/4- SI-B

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.