

FESTO Distributor block FR



Characteristics

Series: FR

Primary thread size in	Secondary connection	Secondary thread size in	Material	Max. operating pressure bar	Temperature °C	Article
G1/8		M5	Aluminum anodized	16	-10 / 60	FR-12-M5
G1/8		M3	Aluminum anodized	16	-10 / 80	FR-9-M3-B
G1/4		G1/4	Aluminium die-cast	16	-10 / 80	FR-4-1/4-C
G1/4	4mm		Aluminium die-cast	8	-10 / 60	FR-12-PK-3-B
G1/4	6mm		Aluminium die-cast	8	-10 / 60	FR-12-PK-4-B
G3/8		G1/8	Aluminium die-cast	16	-10 / 60	FR-8-1/8
G3/8		G3/8	Aluminium die-cast	16	-10 / 80	FR-4-3/8-B
G1/2		G1/4	Aluminium die-cast	16	-10 / 60	FR-8-1/4
G1/2		G1/2	Aluminium die-cast	16	-10 / 80	FR-4-1/2-B
G3/4		G1/2	Aluminium die-cast	16	-10 / 60	FR-8-1/2

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.