



FESTO Service unit combination MSB4

Characteristics

Series: MSB4

Function: Filter-Regulator-Lubricator

Bowl Material: PC

Lockable: Yes

Size	Port thread type	Port Size in	Filtration level µm	With pressure gauge	Drain type	Flow direction	Flow rate l/min	Weight g	Housing material	Article
4	BSPP (G)	1/4	40	Yes	Automatic	left ? right	750	2000	Aluminium die-cast	MSB4-1/4-C3J2D1A1F3-WP
4	BSPP (G)	1/4	5	Yes	Automatic	left ? right	950	1300	Aluminium die-cast	MSB4-1/4-C3J4-WP
4	BSPP (G)	1/4	40	Yes	Automatic	left ? right	1300	1500	Aluminium die-cast	MSB4-1/4-C3J2F3-WP
4	BSPP (G)	1/4	40	Yes	Manual	left ? right	750	1600	Aluminium die-cast	MSB4-1/4:J1D1A1-WP
4	BSPP (G)	1/4	40	Yes	Manual	left ? right	1300	1500	Aluminium die-cast	MSB4-1/4-C3J1F3-WP
4	BSPP (G)	1/4	5	Yes	Manual	left ? right	950	1300	Aluminium die-cast	MSB4-1/4-C3J3-WP
4	BSPP (G)	1/8	40	Yes	Manual	left ? right	850	500	Aluminium die-cast	MSB4-1/8-FRC5-J1M1
4	BSPP (G)	1/4	40	Yes	Automatic	left ? right	900	500	Aluminium die-cast	MSB4-1/4-FRC6-J2M1
4	BSPP (G)	1/4	40	Yes	Manual	left ? right	750	1500	Aluminium die-cast	MSB4-1/4-C3J1M1-WP
4	BSPP (G)	1/4	5	Yes	Manual	left ? right	850	500	Aluminium die-cast	MSB4-1/4-FRC7-J3M1
4	BSPP (G)	1/4	40	Yes	Manual	left ? right	1400	500	Aluminium die-cast	MSB4-1/4-FRC1-J5M1

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.