



COOPER Triple Labyrinth Seal for SRB bearing housings Type: ATL

Aluminium Triple Labyrinth (ATL)

Machined aluminium bodied triple labyrinth seal for high speed and general applications. Supplied as standard in USA and Canada.


Temperature limits: -20°C to +100°C
Maximum speed: Bearing maximum
Shaft surface finish: 3.2 µm Ra

Characteristics

Type: ATL

Temperature range: -20 / 100 °C

Seal material: Aluminium



Manufacturer ID	Shaft diameter mm	Shaft diameter in	Article
ATL208		2.1/2	208ATL-COOPER
ATL40M	40		40MMATL-COOPER
ATL50M	50		50MMATL-COOPER
ATL60M	60		60MMATL-COOPER
ATL70M	70		70MMATL-COOPER
ATL75M	75		75MMATL-COOPER
ATL80M	80		80MMATL-COOPER
ATL85M	85		85MMATL-COOPER
ATL90M	90		90MMATL-COOPER

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.