



FLEXION Adaptor stainless steel AISI 316L male BSPT(R) - female BSPP(G) reducer

Characteristics

- Type: SS-RED-B-T
- Ambient temperature: -20 / 200 °C
- Operation temperature: -40 / 200 °C
- Operating pressure: -0.95 / 150 bar
- Maximum operating pressure [Bar]: 150 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
SS-RED-B-T-1/2M1/4F-FX	Stainless steel 316L	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/4	SS-RED-B-T-1/2M1/4F-FX
SS-RED-B-T-1/2M1/8F-FX	Stainless steel 316L	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/8	SS-RED-B-T-1/2M1/8F-FX
SS-RED-B-T-1/2M3/8F-FX	Stainless steel 316L	External thread BSPT (R)	1/2	Internal thread BSPP (G)	3/8	SS-RED-B-T-1/2M3/8F-FX
SS-RED-B-T-1/4M1/8F-FX	Stainless steel 316L	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/8	SS-RED-B-T-1/4M1/8F-FX
SS-RED-B-T-3/8M1/4F-FX	Stainless steel 316L	External thread BSPT (R)	3/8	Internal thread BSPP (G)	1/4	SS-RED-B-T-3/8M1/4F-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.