



## FLEXION Adaptor stainless steel AISI 316L male BSPP(G) allen key plug with o-ring

### Characteristics

- Type:** SS-PLG-B-HEX-OR  
**Ambient temperature:** -20 / 200 °C  
**Operation temperature:** -40 / 200 °C  
**Operating pressure:** -0.95 / 150 bar  
**Maximum operating pressure [Bar]:** 150 bar

| Manufacturer ID        | Material             | Threaded connection 1    | Connection 1 thread size | Article                |
|------------------------|----------------------|--------------------------|--------------------------|------------------------|
| SS-PLG-B-HEX-OR-1/4-FX | Stainless steel 316L | External thread BSPP [G] | 1/4                      | SS-PLG-B-HEX-OR-1/4-FX |
| SS-PLG-B-HEX-OR-1/8-FX | Stainless steel 316L | External thread BSPP [G] | 1/8                      | SS-PLG-B-HEX-OR-1/8-FX |
| SS-PLG-B-HEX-OR-3/8-FX | Stainless steel 316L | External thread BSPP [G] | 3/8                      | SS-PLG-B-HEX-OR-3/8-FX |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.