



FLEXION Compact ISO21287 cylinder

Characteristics

Type: EPC

Function: Double acting

Magnetic: Yes

Barrel material: Anodised aluminium

Operating temperature: -30 / 80 °C

Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Operating pressure bar	Article
EPC16-20CFDA-FX	Mechanical	16	20	1 / 10	EPC16-20CFDA-FX
EPC16-25CFDA-FX	Mechanical	16	25	1 / 10	EPC16-25CFDA-FX
EPC20-25CFDA-FX	Mechanical	20	25	1 / 10	EPC20-25CFDA-FX
EPC25-50CFDA-FX	Mechanical	25	50	1 / 10	EPC25-50CFDA-FX
EPC40-25CFDA-FX	Mechanical	40	25	1 / 10	EPC40-25CFDA-FX
EPC40-30CFDA-FX	Mechanical	40	30	1 / 10	EPC40-30CFDA-FX
EPC50-50CFDA-FX	Mechanical	50	50	1 / 10	EPC50-50CFDA-FX
EPC63-50CFDA-FX	Mechanical	63	50	1 / 10	EPC63-50CFDA-FX
EPC80-40CFDA-FX	Mechanical	80	40	1 / 10	EPC80-40CFDA-FX
EPC80-50CFDA-FX	Mechanical	80	50	1 / 10	EPC80-50CFDA-FX
EPC100-100CFDA-FX	Mechanical	100	100	1 / 10	EPC100-100CFDA-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.