



FLEXION Piston rod eye DIN648K and ISO8139 for cylinder 8-100mm bore

Characteristics

Type: EPC

Execution	Suitable for diameter mm	Material	Suitable for cylinder	Thread size	Article
Piston rod eye	8, 10	Zinc / Nickel Plated Steel	ISO6432	M4	EPC8-10RODEYE-FX
Piston rod eye	12, 16	Zinc / Nickel Plated Steel	ISO6432	M6	EPC12-16RODEYE-FX
Piston rod eye	20	Zinc / Nickel Plated Steel	ISO6432	M8	EPC20-RODEYE-FX
Piston rod eye	25, 32	Zinc / Nickel Plated Steel	ISO6432, ISO15552	M10x1.25	EPC25-32RODEYE-FX
Piston rod eye	40	Zinc / Nickel Plated Steel	ISO15552	M12x1.25	EPC40-RODEYE-FX
Piston rod eye	50, 63	Zinc / Nickel Plated Steel	ISO15552	M16x1.5	EPC50-63RODEYE-FX
Piston rod eye	80, 100	Zinc / Nickel Plated Steel	ISO15552	M20x1.5	EPC80-100RODEYE-FX

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.