



TSURUMI Submersible pump Series: HS bouwplaatsafwatering

The HS series are 50mm (2") and an 80mm (3") submersible pumps with motor sizes in 400watt and 750watt. The models HS2.75S and HS3.75S offer increased head and flow capability over the HS2.4S. All models have a solid cast aluminium body, cast iron pump casing and an impact resistant PVC strainer base for durability during robust handling. The urethane vortex impeller offers excellent wear resistance in site applications where water contains sand and silt in suspension, thus maintaining performance and reliability. The 750watt pumps feature an oil lifter to maintain seal lubrication during operation in any position. All models have a 403 stainless steel shaft, that is fitted with an ultra hardwearing, double mechanical seal (inboard: silicon carbide - silicon carbide) – which runs in an oil chamber - and have a stirring device to reduce blockages. Used predominantly as contractor pumps on site drainage duties, they can also be used in other industrial applications. Supplied with 10 metres of heavy duty, rubber power cable. Available in single-phase only with an optional float switch.

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.