SMC One-touch Fittings Manifold series KM



Characteristics Series: KM Type: KM12

Primary connection	Primary thread size	Secondary connection	Material	Max. operating pressure	Temperature	Article
	in			bar	°C	
4 mm			PBT	10	-5 / 60	KM13-04-06-3
4 mm		8 mm	PBT	10	-5 / 60	KM13-04-08-3
4 mm		8 mm	PBT	10	-5 / 60	KM11-04-08-6
4 mm		8 mm	PBT	10	-5 / 60	KM11-04-08-10
6 mm		6 mm	PBT	10	-5 / 60	KM16-06-06-3
6 mm		10 mm	PBT	10	-5 / 60	KM11-06-10-10
6 mm		10 mm	PBT	10	-5 / 60	KM11-06-10-6
6 mm	R1/4		PBT	10	-5 / 60	KM12-06-02-6
6 mm	R1/4		PBT	10	-5 / 60	KM12-06-02-10
8 mm		8 mm	PBT	10	-5 / 60	KM13-06-08-3
8 mm		8 mm	PBT	10	-5 / 60	KM11-08-12-10
8 mm		8 mm	PBT	10	-5 / 60	KM11-08-12-6
10 mm		10 mm	PBT	10	-5 / 60	KM13-06-10-3
10 mm		10 mm	PBT	10	-5 / 60	KM13-08-10-3

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR9585710142116727_EN_07.05.2024