FORMAT Digital pocket caliper with absolute value function and data output type 4020



DIN 862	RVS	Absolut- System	RS232	USB	Digimatic	Ø 1,5 mm

Design: Made of stainless steel, hardened, measuring faces precision ground, with locking screw, digit height of LCD 7.5 mm, inductive measurement system, with data output variable RS 232, USB and Digimatic [DATA Variable]. Supplied with battery CR 2032, 3 V, in plastic case.

Function: On and automatic off switch, mm/inch switching, automatic switching by means of slider movement, key lock set for zero position, re-zeroing after switching deleted (absolute system), reset (zeroing) possible at each position, ± pre-set function (setting a numerical value).

Application: For inner, outer, depth and step measurements.

Note: Replacement battery (Order No. 4027 2032). Data cable USB (Order No. 4025 0003). Data cable Digimatic (Order No. 4025 0004). Data cable RS 232 available on request.

Measuring range	Digital indication	Article	
mm			
0 / 150	Yes	W90A-40201200	
0 / 150	Yes	W90A-40201205	
0 / 200	Yes	W90A-40201220	
0 / 300	Yes	W90A-40201300	

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR_EC000157_0025_MVB_EN_18.05.2024