

GUHRING Ratio drill with oil feed type 6511



Deep hole drill, 20 x D

RT 100 T method:
?

Characteristics


Cutting direction: Right

Type: Twist drill

Coating: TiAlN

Cooling channel(Oil feed): 1

Point angle: 135 °



Diameter mm	Cutting length mm	Total length mm	Holding system	Material	Article
3	70	110	Cylindrical	Solid carbide	W90A-12340300
3.5	96	136	Cylindrical	Solid carbide	W90A-12340350
4	96	136	Cylindrical	Solid carbide	W90A-12340400
4.5	118	158	Cylindrical	Solid carbide	W90A-12340450
5	118	158	Cylindrical	Solid carbide	W90A-12340500
5.5	140	180	Cylindrical	Solid carbide	W90A-12340550
6	140	180	Cylindrical	Solid carbide	W90A-12340600
6.5	162	202	Cylindrical	Solid carbide	W90A-12340650
7	162	202	Cylindrical	Solid carbide	W90A-12340700
7.5	183	223	Cylindrical	Solid carbide	W90A-12340750
8	183	223	Cylindrical	Solid carbide	W90A-12340800
9	205	249	Cylindrical	Solid carbide	W90A-12340900
10	227	271	Cylindrical	Solid carbide	W90A-12341000
12	274	323	Cylindrical	Solid carbide	W90A-12341200
14	318	367	Cylindrical	Solid carbide	W90A-12341400

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.