

GUHRING Ratio drill with oil feed type 6513



Deep hole drill, 30 x D

RT 100 T method:
?

Characteristics

Cutting direction: Right

Type: Twist drill

Coating: TiAlN

Cooling channel(Oil feed): 1

Point angle: 135 °



Diameter mm	Cutting length mm	Total length mm	Holding system	Material	Article
3	100	140	Cylindrical	Solid carbide	W90A-12360300
4.5	168	208	Cylindrical	Solid carbide	W90A-12360450
5	168	208	Cylindrical	Solid carbide	W90A-12360500
5.5	200	240	Cylindrical	Solid carbide	W90A-12360550
6	200	240	Cylindrical	Solid carbide	W90A-12360600
6.5	232	272	Cylindrical	Solid carbide	W90A-12360650
7	232	272	Cylindrical	Solid carbide	W90A-12360700
8	263	303	Cylindrical	Solid carbide	W90A-12360800
8.5	295	339	Cylindrical	Solid carbide	W90A-12360850
9	295	339	Cylindrical	Solid carbide	W90A-12360900
10	327	371	Cylindrical	Solid carbide	W90A-12361000

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.