## FORMAT Centring drill type 1129



Design: HSS, DIN 333-R, with radius (minimal danger of breaking), 60° countersink angle, profile grinding, bright surface. Ø tolerance:

## **Characteristics**

Cutting direction: Right DIN standard: 333-R Type: Center drill Point angle: 60 °

Diameter	Total length	Holding system	Material	Article
mm	mm			
1	31.5	Cylindrical	HSS	W90A-11290100
1.25	31.5	Cylindrical	HSS	W90A-11290125
1.6	35.5	Cylindrical	HSS	W90A-11290160
2	40	Cylindrical	HSS	W90A-11290200
2.5	45	Cylindrical	HSS	W90A-11290250
3.15	50	Cylindrical	HSS	W90A-11290315
4	56	Cylindrical	HSS	W90A-11290400
5	63	Cylindrical	HSS	W90A-11290500
6.3	71	Cylindrical	HSS	W90A-11290630

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

T

