## **FORMAT Centring drill type 1132**









Design: HSS, DIN 333-B, 60/120° countersink angle, profile grinding, bright surface.  $\varnothing$  tolerance:

## **Characteristics**

Cutting direction: Right DIN standard: 333-B
Type: Center drill

Total length	Holding system	Material	Article
mm			
40	Cylindrical	HSS	W90A-11320125
45	Cylindrical	HSS	W90A-11320160
50	Cylindrical	HSS	W90A-11320200
56	Cylindrical	HSS	W90A-11320250
60	Cylindrical	HSS	W90A-11320315
67	Cylindrical	HSS	W90A-11320400
75	Cylindrical	HSS	W90A-11320500
80	Cylindrical	HSS	W90A-11320630
	mm 40 45 50 56 60 67 75	mm  40 Cylindrical 45 Cylindrical 50 Cylindrical 56 Cylindrical 60 Cylindrical 67 Cylindrical 75 Cylindrical	mm         Cylindrical         HSS           45         Cylindrical         HSS           50         Cylindrical         HSS           56         Cylindrical         HSS           60         Cylindrical         HSS           67         Cylindrical         HSS           75         Cylindrical         HSS

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**ERIKS**