

FORMAT SDS Plus hammer drill type 1250



Design: Hammer drill with SDS-plus shank Effective drilling dust removal due to the aggressive tip and twist design. Certified by the Prüfgemeinschaft Mauerbohrer (PGM) according to the requirements of the Deutschen Instituts für Bautechnik (DIBt).

Application: Concrete, limestone, masonry.

* Pre-drill at least 150 mm deep with a short drill of the same diameter.

** Designed as a twist hammer drill

Characteristics

Cutting direction: Right

Type: Hammer drill

Diameter mm	Cutting length mm	Total length mm	Holding system	Article
4	50	110	SDS-plus	W90A-12500411
5	50	110	SDS-plus	W90A-12500511
5	100	160	SDS-plus	W90A-12500516
6	50	110	SDS-plus	W90A-12500611
6	100	160	SDS-plus	W90A-12500616
6	150	210	SDS-plus	W90A-12500621
6	200	260	SDS-plus	W90A-12500626
7	100	160	SDS-plus	W90A-12500716
8	50	110	SDS-plus	W90A-12500811
8	100	160	SDS-plus	W90A-12500816
8	150	210	SDS-plus	W90A-12500821
8	200	260	SDS-plus	W90A-12500826
8	250	310	SDS-plus	W90A-12500831
8	400	460	SDS-plus	W90A-12500846
10	50	110	SDS-plus	W90A-12501011
10	100	160	SDS-plus	W90A-12501016
10	150	210	SDS-plus	W90A-12501021
10	200	260	SDS-plus	W90A-12501026
10	250	310	SDS-plus	W90A-12501031
10	400	460	SDS-plus	W90A-12501046
12	100	160	SDS-plus	W90A-12501216
12	150	210	SDS-plus	W90A-12501221
12	200	260	SDS-plus	W90A-12501226
12	250	300	SDS-plus	W90A-12501230
12	400	460	SDS-plus	W90A-12501246
12	550	600	SDS-plus	W90A-12501260
14	100	160	SDS-plus	W90A-12501416
14	150	210	SDS-plus	W90A-12501421
14	200	260	SDS-plus	W90A-12501426
14	250	310	SDS-plus	W90A-12501431
14	400	460	SDS-plus	W90A-12501446
14	550	600	SDS-plus	W90A-12501460
15	100	160	SDS-plus	W90A-12501516
15	200	260	SDS-plus	W90A-12501526
16	100	150	SDS-plus	W90A-12501615

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Diameter mm	Cutting length mm	Total length mm	Holding system	Article
16	150	210	SDS-plus	W90A-12501621
16	200	250	SDS-plus	W90A-12501625
16	250	300	SDS-plus	W90A-12501630
16	400	450	SDS-plus	W90A-12501645
16	550	600	SDS-plus	W90A-12501660
18	150	200	SDS-plus	W90A-12501820
18	200	250	SDS-plus	W90A-12501825
18	250	300	SDS-plus	W90A-12501830
18	400	450	SDS-plus	W90A-12501845
20	150	200	SDS-plus	W90A-12502020
20	250	300	SDS-plus	W90A-12502030
20	400	450	SDS-plus	W90A-12502045
22	400	450	SDS-plus	W90A-12502245
24	400	450	SDS-plus	W90A-12502445
25	400	450	SDS-plus	W90A-12502545
				W90A-12502645
				W90A-12501321

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.