FORMAT Masonry drill type 1259

Design: With round shank. The computer calculated twist profile ensures optimum removal of drilling dust, smoother drilling and optimum impact energy transport. Extremely long tool lives are achieved by the high strength soldering of carbide plates and the annealed surface, which results in a guaranteed higher break-resistance in impacts and higher strength for armouring hits. Up to 50% more holes than standard concrete drills. Certified by the Prüfgemeinschaft Mauerbohrer.

Application: For concrete, stone, masonry, brick, light construction materials, granite and marble.

Characteristics

Cutting direction: Right
Type: Stone drill

Diameter mm	Cutting length mm	Total length mm	Holding system	Article
3	40	70	Cylindrical	W90A-12590300
4	40	75	Cylindrical	W90A-12590400
5	50	85	Cylindrical	W90A-12590500
6	60	100	Cylindrical	W90A-12590600
7	60	100	Cylindrical	W90A-12590700
8	80	120	Cylindrical	W90A-12590800
9	80	120	Cylindrical	W90A-12590900
10	80	120	Cylindrical	W90A-12591000
12	90	150	Cylindrical	W90A-12591200
14	90	150	Cylindrical	W90A-12591400
16	100	160	Cylindrical	W90A-12591600

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC000945_0626_EN_20.04.2024

ERIKS UK | Tel: 01384 276659 | E-mail: tools.support@eriks.co.uk