

## FORMAT Counterbore, core hole, HSS type 1406

|            |        |
|------------|--------|
| DIN<br>373 | Z<br>3 |
|------------|--------|



Design: HSS, DIN 373.  
Spiral fluted with fixed pilot pin

Application: For countersinking inner hexagon screws DIN 912, DIN 6912 and DIN 7984 as well as cylinder screws DIN 84 (ISO 1207).

Note: The countersink pilot pins only fit in the thread core holes.

### Characteristics

**Cutting direction:** Right

**Type:** Countersinking cutter

| Diameter<br>mm | Total length<br>mm | Holding system | Material | Article       |
|----------------|--------------------|----------------|----------|---------------|
| 6              | 71                 | Cylindrical    | HSS      | W90A-14060300 |
| 8              | 71                 | Cylindrical    | HSS      | W90A-14060400 |
| 10             | 80                 | Cylindrical    | HSS      | W90A-14060500 |
| 11             | 80                 | Cylindrical    | HSS      | W90A-14060600 |
| 15             | 100                | Cylindrical    | HSS      | W90A-14060800 |
| 18             | 100                | Cylindrical    | HSS      | W90A-14061000 |
| 20             | 100                | Cylindrical    | HSS      | W90A-14061200 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.