

FORMAT Counterbore, HSS for continuous holes with morse taper shank hole type 1412



Design: HSS.
Spiral fluted with fixed pilot pin

Application: For countersinking inner hexagon screws DIN 912, DIN 6912 and DIN 7984 as well as cylinder screws DIN 84 (ISO 1207).

Note: Further dimensions available on request.

Characteristics

Cutting direction: Right

Type: Countersinking cutter

Diameter mm	Total length mm	Holding system	Material	Article
18	150	Morseconus 2	HSS	W90A-14151000
18	150	Morseconus 2	HSS	W90A-14121000
20	150	Morseconus 2	HSS	W90A-14151200
20	150	Morseconus 2	HSS	W90A-14121200
24	160	Morseconus 2	HSS	W90A-14151400
24	160	Morseconus 2	HSS	W90A-14121400
26	190	Morseconus 3	HSS	W90A-14121600
26	190	Morseconus 3	HSS	W90A-14151600
30	190	Morseconus 3	HSS	W90A-14151800
30	190	Morseconus 3	HSS	W90A-14121800
33	190	Morseconus 3	HSS	W90A-14152000
33	190	Morseconus 3	HSS	W90A-14122000
36	205	Morseconus 3	HSS	W90A-14152200
36	205	Morseconus 3	HSS	W90A-14122200
40	205	Morseconus 3	HSS	W90A-14122400
40	205	Morseconus 3	HSS	W90A-14152400

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.