

## FORMAT Cable lug - connection plug set type 5567

Design: Insulated ring and pin cable lugs, shock connectors and flat push-on contacts, conductor cross-section from 0.5?6 mm<sup>2</sup>. Supplied in plastic case with removable inserts.

Each 250 ferrules 4; 6 mm<sup>2</sup>

each 500 ferrules 0.5; 0.75; 1; 1.5; 2.5 mm<sup>2</sup>

each 100 ring cable lugs 0.5?1.5 (M4); 0.5?1.5 (M5); 1.5?2.5; 4.0?6.0 mm<sup>2</sup>

each 100 pin cable lugs 0.5?1.5; 1.5?2.5; 4.0?6.0 mm<sup>2</sup>

each 100 shock connectors 0.5?1.5; 1.5?2.5; 4.0?6.0 mm<sup>2</sup>

each 100 flat ferrules 0.5?1.5 (2.8 mm); 0.5?1.5 (6.3 mm); 1.5?2.5; 4.0?6.0 mm<sup>2</sup>





| Description                                    | Article       |
|--|---------------|
| Term. sleeve / cable-lug assortment 4400-piece | W90A-55670010 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR\_EC001052\_0002\_MVB\_EN\_04.05.2024 Page 1/1