KUKKO Universal pulley extractor, Twin arms with narrow tow hooks type 20

SEE PIX ARMIOCK

Design: With sliding, always parallel and switchable puller legs made of chrome alloy tool steel and tempered, specially coated pressure spindle with especially good sliding characteristics.

Application: With switchable puller legs, suitable as external and recessed extractor.

Optimised geometry of traverse and sliders for particularly easy movement of the puller legs. At the same time, ensures a firm grip when tightening the screws.

Novel cross hook ensures maximum stability of the suspension in slider and hooks. Quick changes, because only one screw is necessary.

Clamping spread	Clamping reach	Article
mm	mm	
90	100	W90A-69050090
120	100	W90A-69050120
160	150	W90A-69050160
200	150	W90A-69050200
250	200	W90A-69050250
350	200	W90A-69050350
520	200	W90A-69050520
650	300	W90A-69050650

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR_EC002110_0236_MVB_EN_20.05.2024