

FORMAT Try squaretype 4604

DIN 875/II

Design: Made of special steel, rectangularity, parallelism and planarity tolerances, flat sides, high edges and test surfaces ground.

Application: For precise work in mechanical engineering and in the workshop.

Note: Flat square (Order No. 4611) and stop angle (Order No. 4612) available up to 2000 mm on request.

| Length long shank | Leg length | Article |
|-------------------|------------|---------------|
| mm | mm | |
| 75 | 50 | W90A-46040075 |
| 100 | 70 | W90A-46040100 |
| 150 | 100 | W90A-46040150 |
| 200 | 130 | W90A-46040200 |
| 250 | 165 | W90A-46040250 |
| 300 | 175 | W90A-46040300 |
| 400 | 200 | W90A-46040400 |
| 500 | 250 | W90A-46040500 |
| 750 | 375 | W90A-46040750 |
| 1000 | 500 | W90A-46041000 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC002111_0008_MVB_EN_12.05.2024