

FORMAT 3-part hand tap set HSS metric type 1604



HSS

DIN 352

ISO 2 6H

Typ N

Design: HSS, DIN 352, tolerance range ISO 2/6H, type N, bright surface.

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Set consisting of {order no. 1600, 1601, 1603}.

Characteristics

Kind of thread: Metric

DIN standard: 352

Kind of thread	Thread size metric (M...)	Pitch inner thread	DIN standard	Material	Total length	Article
		mm			mm	
Metric	1		352	HSS		W90A-16040010
Metric	1.2		352	HSS		W90A-16040012
Metric	1.4		352	HSS		W90A-16040014
Metric	1.6		352	HSS		W90A-16040016
Metric	1.7		352	HSS		W90A-16040017
Metric	2		352	HSS		W90A-16040020
Metric	2.2		352	HSS		W90A-16040022
Metric	2.3		352	HSS		W90A-16040023
Metric	2.5		352	HSS		W90A-16040025
Metric	2.6		352	HSS		W90A-16040026
Metric	3.5		352	HSS		W90A-16040035
Metric	4		352	HSS		W90A-16040040
Metric	4.5		352	HSS		W90A-16040045
Metric	5		352	HSS		W90A-16040050
Metric	6		352	HSS		W90A-16040060
Metric	7		352	HSS		W90A-16040070
Metric	8		352	HSS		W90A-16040080
Metric	9	1.25	352	HSS	63	W90A-16040090
Metric	10		352	HSS		W90A-16040100
Metric	11		352	HSS		W90A-16040110
Metric	14		352	HSS		W90A-16040140
Metric	16		352	HSS		W90A-16040160
Metric	18		352	HSS		W90A-16040180
Metric	20		352	HSS		W90A-16040200
Metric	22		352	HSS		W90A-16040220
Metric	24		352	HSS		W90A-16040240
Metric	27		352	HSS		W90A-16040270
Metric	30		352	HSS		W90A-16040300
Metric			352	HSS		W90A-16040030
Metric			352	HSS		W90A-16040120

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.