


FORMAT 3-part hand tap set HSS metric left type 1612



Design: HSS, DIN 352, tolerance range ISO 2/6H, type N, bright surface.

3 piece set consisting of roughing tap with point form A (6?8 threads), second tap with point form D (3.5?5 threads) and finish tap with point form C (2?3 threads).

Application: For metric left threads according to DIN ISO 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Characteristics

Kind of thread: Metric

DIN standard: 352

Kind of thread	Thread size metric [M..]	DIN standard	Material	Article
Metric	3	352	HSS	W90A-16120030
Metric	4	352	HSS	W90A-16120040
Metric	5	352	HSS	W90A-16120050
Metric	6	352	HSS	W90A-16120060
Metric	8	352	HSS	W90A-16120080
Metric	10	352	HSS	W90A-16120100
Metric	12	352	HSS	W90A-16120120
Metric	14	352	HSS	W90A-16120140
Metric	16	352	HSS	W90A-16120160
Metric	18	352	HSS	W90A-16120180
Metric	20	352	HSS	W90A-16120200

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.