
FORMAT 3-part hand tap set HSS metric fine type 1618





Design: HSS-E, DIN 352, tolerance range ISO 2/6H, type INOX, bright surface.

3 piece set consisting of roughing tap with point form A (6?8 threads), second tap with point form D (3.5?5 threads) and finish tap with point form C (2?3 threads).

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Characteristics

Kind of thread: Metric DIN standard: 352

Kind of thread	Thread size metric (M)	Pitch inner thread	DIN standard	Material	Total length	Article
		mm			mm	
Metric	2	0.4	352	HSS-co	36	W90A-16180020
Metric	2.5	0.45	352	HSS-co	40	W90A-16180025
Metric	3	0.5	352	HSS-co	40	W90A-16180030
Metric	3.5	0.6	352	HSS-co	45	W90A-16180035
Metric	4	0.7	352	HSS-co	45	W90A-16180040
Metric	5	0.8	352	HSS-co	50	W90A-16180050
Metric	6	1	352	HSS-co	50	W90A-16180060
Metric	8	1.25	352	HSS-co	56	W90A-16180080
Metric	10		352	HSS-co		W90A-16180100
Metric	12	1.75	352	HSS-co	75	W90A-16180120
Metric	14	2	352	HSS-co	80	W90A-16180140
Metric	16	2	352	HSS-co	80	W90A-16180160
Metric	20	2.5	352	HSS-co	95	W90A-16180200

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: tools.support@eriks.co.uk

ERIKS