


FORMAT 3-part hand tap set HSS BSW type 1635



Design: HSS, DIN 2184, type N, bright surface.

Consisting of roughing tap with point form A [6?8 threads], second tap with point form D [3.5?5 threads] and finish tap with point form C [2?3 threads].

Application: For Whitworth threads according to DIN 11. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Characteristics

Kind of thread: BSW

DIN standard: 2184

Kind of thread	Thread size in	Pitch inner thread in	DIN standard	Material	Article
BSW			2184	HSS	W90A-16350001
BSW			2184	HSS	W90A-16350023
BSW			2184	HSS	W90A-16350013
BSW			2184	HSS	W90A-16350019
BSW			2184	HSS	W90A-16350021
BSW	1/2	12	2184	HSS	W90A-16350017
BSW	1/4	20	2184	HSS	W90A-16350009
BSW	1	8	2184	HSS	W90A-16350027
BSW	3/16	24	2184	HSS	W90A-16350005
BSW	5/16	18	2184	HSS	W90A-16350011
BSW	5/32	32	2184	HSS	W90A-16350003
BSW	7/16	14	2184	HSS	W90A-16350015
BSW	7/32	24	2184	HSS	W90A-16350007
BSW	7/8	9	2184	HSS	W90A-16350025

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.