



FACOM Combination spanner OGV, metric type no. 440

- Standard wrench for all current applications
- More comfortable due to the variable handle cross section which doubles the surface area in contact with the hand allowing painless torque application
- High mechanical strength combined with compact sizes meeting aeronautical standards
- Satin chrome finish
- Ring head - Ring open end designed for better access to series or embedded screws
- Ring head angled at 15°
- Open end head - angled at 15°
- Open end head-handle geometry optimised for increased access

Characteristics

Low spark model: No

Model	Wrench width mm	Length mm	Low spark model	Weight g	Article
					FAC440.30
Metric	4	106		10	FAC440.4H
Metric	5.5	115		15	FAC440.5.5H
Metric	6	115		20	FAC440.6
Metric	7	122		20	FAC440.7
Metric	8	133	No	30	FAC440.8
Metric	9	138		35	FAC440.9
Metric	10	145	No	40	FAC440.10
Metric	11	155	No	50	FAC440.11
Metric	12	162		60	FAC440.12
Metric	13	170	No	70	FAC440.13
Metric	14	180	No	85	FAC440.14
Metric	15	185		95	FAC440.15
Metric	16	195		115	FAC440.16
Metric	17	202	No	130	FAC440.17
Metric	18	208		150	FAC440.18
Metric	19	216	No	170	FAC440.19
Metric	20	224		185	FAC440.20
Metric	21	233		205	FAC440.21
Metric	22	248	No	230	FAC440.22
Metric	23	267		255	FAC440.23
Metric	24	267	No	290	FAC440.24
Metric	25	274		315	FAC440.25
Metric	26	285		345	FAC440.26
Metric	27	295	No	375	FAC440.27
Metric	28	305		415	FAC440.28
Metric	29	320		475	FAC440.29
Metric	32	355	No	640	FAC440.32
Metric	33	380		715	FAC440.33
Metric	34	390		745	FAC440.34
Metric	36	440		945	FAC440.36

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.