

## FORMAT Screw clamp, wooden handle, no anti-slip type 5091

Design: Hollow profile rail made from statically optimised, cold-drawn quality steel, 6-way serrated and zincplated, fixed and mobile brackets made from high-quality, powder-coated cast iron, spindle with trapezoidal thread, burnished, with wooden handle, and mobile-mounted, completely flat pressure plate. The screw clamps to jaw width 400 mm, fitted with plastic protective caps on the pressure plate and on the upper part for gentle clamping.

Application: Multi-purpose clamping tool for holding items for processing or connecting to other parts.

| Chucking range | Jaw length | Article       |
|----------------|------------|---------------|
| mm             | mm         |               |
| 2              | 120        | W90A-50910200 |
| 100            | 50         | W90A-50910010 |
| 120            | 60         | W90A-50910012 |
| 120            | 120        | W90A-50910080 |
| 160            | 80         | W90A-50910016 |
| 200            | 100        | W90A-50910020 |
| 250            | 120        | W90A-50910025 |
| 300            | 140        | W90A-50910030 |
| 400            | 175        | W90A-50910040 |
| 500            | 120        | W90A-50910050 |
| 600            | 120        | W90A-50910060 |
| 1000           | 120        | W90A-50910100 |
| 1250           | 120        | W90A-50910125 |
| 1500           | 120        | W90A-50910150 |
| 2500           | 120        | W90A-50910250 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

FRIK



**ERIKS UK**