

## **BESSEY All steel bench fitter clamp SGM**

Design: Fixed bracket and pressure plate manufactured from one piece of Special steel; warp-resistant. Newly designed, U-shaped mobile bracket made of forged heat-treatable steel. Greatest security thanks to linear force transmission at the new mobile bracket. Heat-resistant, high-performance pressure plate with large ball coupling, can be pivoted 35° and replaced, with hardened and oil-soaked sintered steel insert. 20% more clamping force per spindle rotationdue to optimised rail profile.

Application: Especially for clamping forces up to 12 kN. As such, it can be used for all metal processing and in steel construction, as well as in woodworking.

Chucking range	Jaw length	Article
mm	mm	
1	140	W90A-51011000
250	140	W90A-51010250
300	140	W90A-51010300
500	140	W90A-51010500
800	140	W90A-51010800
1250	140	W90A-51011250
1500	140	W90A-51011500

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR\_EC002200\_0039\_MVB\_EN\_05.05.2024 Page 1/1