



## FORMAT Solid steel gluing clamp type 5106

Design: Slide rail, fixed bracket and pressure plate manufactured from one piece of structurally optimised, cold-drawn profile steel. Mobile bracket made of forged, galvanised zinc-plated heat-treatable steel, smooth-running spindle with rolled, cold-twisted, burnished trapezoidal thread, with wooden handle and mobile pressure plate.

Application: Flexible clamping for the sensitive holding of items. For high clamping forces with low tool weight.

| Chucking range<br>mm | Jaw length<br>mm | Article       |
|----------------------|------------------|---------------|
| 1                    | 120              | W90A-51060100 |
| 100                  | 50               | W90A-51060010 |
| 120                  | 60               | W90A-51060012 |
| 160                  | 80               | W90A-51060016 |
| 200                  | 100              | W90A-51060020 |
| 250                  | 120              | W90A-51060025 |
| 300                  | 140              | W90A-51060030 |
| 400                  | 120              | W90A-51060040 |
| 500                  | 120              | W90A-51060050 |
| 600                  | 120              | W90A-51060060 |
| 800                  | 120              | W90A-51060080 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.