



## ECON® Globe valve Type: 254 Bronze Flange PN32



### Characteristics

- Type:** 254
- Norm:** EN (DIN)
- Construction type:** Straight
- Housing material:** Bronze
- Connection:** Flange
- Flange finish:** Flat face
- Stem seal type:** Gland seal
- Material disc:** Stainless steel
- Spindle material:** CuZn41Pb2
- Primary spindle seal material:** Fiber Gasket
- Material bonnet:** G-CuSn5ZnPb [Rg5]

### Characteristics [2]

- Bonnet gasket material:** Fiber Gasket
- Actuator material:** Aluminium
- Minimum medium temperature (continuous):** -10 °C
- Maximum medium temperature (continuous):** 185 °C
- Maximum pressure difference at 20 °C:** 32 bar

DN [mm]	Pressure rating	A mm	L mm	H mm	M mm	Weight [kg]
15	PN 32	95	80	116	60	1,7
20	PN 32	105	90	126	60	2,3
25	PN 32	115	100	144	70	3,1
32	PN 32	140	110	165	90	5
40	PN 32	150	130	171	90	5,9
50	PN 32	165	150	207	110	8,9

Bore	0/100°C	140°C	185°C	
DN 15 - 50	32	25	16	[bar]

Material quality	Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face norm	Face to Face length mm	Operation	Type of disc	Type of bonnet	Sealing	Article
G-CuSn5ZnPb (Rg5)	DN20	PN32	PN16	Manufacturer standard	90	Hand wheel, rising with rising stem	Fixed disc	Screwed	PTFE	EC00254002-0BG13
G-CuSn5ZnPb (Rg5)	DN25	PN32	PN16	Manufacturer standard	100	Hand wheel, rising with rising stem	Fixed disc	Screwed	PTFE	EC00254002-5BG13

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.