

ARI Rayon heating patent valve Series: 12.076 Type: 2430 Cast iron Internal thread (BSPP) PN16

Cast iron Rayon CV globe valve, soft seated with BSP thread ends, pressure class PN16

Characteristics Series: 12.076 Type: 2430 Norm: EN (DIN) Construction type: Straight Housing material: Cast iron Surface protection: Standard manufacturers coating Connection: Internal thread (BSPP) Stem seal type: Gland seal Primary spindle seal material: EPDM Material isolation cap: Plastic

Application

- Utility installations and industry.
- Heating, cooling, ventilation and air conditioning systems (HVAC).
- Closed or circulation systems.
- Neutral liquids and gases.
- Recommended in: Utilities

Technical Information

- Extremely low flow resistance.
- Maintenance-free stem seal.
- Simple and easy to insulate.
- Suitable for control function.
- With position indicator.
- With stroke limiter and locking device.
- •

DN	L	н	м	Weight	Kv
["]	[mm]	mm	mm	[kg]	[m3/hr]
1/2	115	190	110	2,5	15,3
3/4	120	190	110	2,8	21,6
1	125	190	110	3,1	31,1
1 1⁄4	130	190	110	3,2	50
1 1⁄2	140	215	140	5,2	62
2	150	225	140	6,2	91

Temperature range	Max. oper. press.
-10°C / 120°C	16 bar
brief 130°C	

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

EKIK

Т