

ECON® Gate valve Type: 317 Cast iron With position indicator Flange PN6/16

Characteristics

Type: 317 Norm: EN (DIN) Housing material: Cast iron Surface protection: Standard manufacturers coating Connection: Flange Stem seal type: Gland seal With position indicator: Yes Primary spindle seal material: PTFE Material bonnet: EN-JL1040

Characteristics (2)

Bonnet gasket material: Fiber Gasket Actuator material: Cast iron Minimum medium temperature (continuous): -10 °C Maximum medium temperature (continuous): 150 °C Maximum pressure difference at 20 °C: 10 bar

DN	А	L	HI	М	Drain plug	Weight
[mm]	mm	mm	mm	mm	G ["]	[kg]
40	150	140	243	125		10
50	165	150	270	150	1/2	12
65	185	170	306	175	1/2	15
80	200	180	343	175	1/2	18
100	220	190	383	200	1/2	23
125	250	200	443	200	1/2	33
150	285	210	505	225	1/2	43
200	340	230	596	225	3/4	65
250	395	250	708	250	3/4	92
300	445	270	794	300	3/4	135
350	505	290	997	400	1	207
400	565	310	1087	400	1	246
500	670	350	1308	500	1	416
600	780	390	1493	500	1	624

Size	Hot water	Other media
DN 40 thru DN 300	8 bar- 150°C	10 bar- 120°C
DN 350 thru DN 500	2 bar- 150°C	6 bar- 120°C
DN 600		2,5 bar- 120°C

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length mm	Operation	Type of bonnet	Sealing	Wedge material	Spindle material	Article
EN-JL1040	DN40	PN10	EN 558, Series 14	140	Hand wheel, non-rising with non- rising stem	Bolted bonnet	Bronze	Bronze	CW614N	EC003170040- FDB2

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/2

PR_EC010163_0023_MVD_EN_27.07.2024



Gate Valves | Gate Valves with Flange Connection

Material quality	Nominal inner diameter	Pressure rating	Face to Face norm	Face to Face length	Operation	Type of bonnet	Sealing	Wedge material	Spindle material	Article
				mm						
EN-JL1040	DN50	PN10	EN 558, Series 14	150	Hand wheel, non-rising with non- rising stem	Bolted bonnet	Bronze	Bronze	CW614N	EC003170050- FDB2
EN-JL1040	DN65	PN10	EN 558, Series 14	170	Hand wheel, non-rising with non- rising stem	Bolted bonnet	Bronze	Bronze	CW614N	EC003170065- FDB2
EN-JL1040	DN80	PN10	EN 558, Series 14	180	Hand wheel, non-rising with non- rising stem	Bolted bonnet	Bronze	Bronze	CW614N	EC003170080- FDB2
EN-JL1040	DN150	PN10	EN 558, Series 14	210	Hand wheel, non-rising with non- rising stem	Bolted bonnet	Bronze	Cast iron	CW614N	EC003170150F- DB2

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

