



## ECON® Needle valve Type: 226 Stainless steel Straight T-bar Internal thread (BSPP)}

### Characteristics

**Type:** 226  
**Norm:** EN (DIN)  
**Construction type:** Straight  
**Housing material:** Stainless steel  
**Material quality:** 1.4401  
**Connection:** Internal thread (BSPP)  
**Face to Face norm:** Manufacturer standard  
**Operation:** T-bar  
**Rotating needle:** Yes

**Spindle material:** 1.4401

**Actuator material:** 1.4305

**Minimum medium temperature (continuous):** -10 °C

**Maximum medium temperature (continuous):** 250 °C

### Application

- Recommended in: Food & Beverages

Thread connection ["]	d mm	L mm	H (open) mm	M mm
1/4	3	50	78	50
3/8	5	55	78	50
1/2	6	60	80	50
3/4	8	80	97	60
1	8	80	99	60

Max. operating pressure	Max. medium temperature
420 bar	20°C
320 bar	200°C
250 bar	250°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.