

ECON® Pressure gauge valve Type 868 stainless steel internal/external thread



Characteristics

Type: 868

Housing material: Stainless steel

Material quality: 1.4571

Operation: Hand wheel

Material tension socket: Stainless steel


Material swivel nut: Stainless steel

Application

- Liquids, gases and vapours.
- Process industry.
- Machine building.
- Chemical and petrochemical industry.
- Oil- and gas industry.
- Power plants.
- Recommended in: Chemical

Technical Information

- According to DIN 16270 form A.
- With venting screw.
- Tension socket connection according to DIN 16283.
- Type 868M provided with inspection connection M20 x 1.5.



Process connection	Size process connection	Connection instrument side	Size instrument connection	Inspection connection	Pressure rating	Maximum pressure at 20 °C bar	Maximum medium temperature (continuous) °C	Primary spindle seal material	Spindle material	Article
External thread	1/2" BSPP(G)	Tension socket	1/2" BSPP(G)	M20x1.5	PN400	400	200	PTFE	1.4571	EC0861M01/2-MACCACO
External thread	1/2" BSPP(G)	Tension socket	1/2" BSPP(G)	None	PN400	400	300	Graphite	1.4571	EC0086801/2-EFBH-GRAPH
External thread	1/4" BSPP(G)	Tension socket	1/4" BSPP(G)	None	PN250	250	200	PTFE	1.4571	515456

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.