

0 00000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 00000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 00000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 0000 0 00000 0 000

PARKER Flowmeter fig. 8144 air

Characteristics

Series: FM26 Type: 8144

Mounting: Horizontal and vertical

Internal spring: Yes

Process connection: Internal thread (BSPP)

Calibration: Air Accuracy: 5.0 %

Material of connection: Brass, Nickel-plated

Housing material: PC

Sealing: FPM

Characteristics (2)

Spring material: Stainless steel 302 **Material float catcher:** Brass, Nickel-plated

With needle valve: No Explosion-proof: No

Medium temperature: -20 / 90 °C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



PR_EC010586_0020_MVD_EN_27.04.2024