

GRUNDFOS Submersible pump Series: Unilift AP RVS vuilwaterpomp



Characteristics

Series: Unilift AP

Connection: Internal thread (BSPP)

Material pump casing: Stainless steel

Material quality: 1.4301

Insulation class acc. to IEC: F

| Maximum flow rate | Nominal volume flow rate | Max. immersion depth | Supply voltage | Length connecting cord | Rotational speed | Nominal current | Connection size | Pump height | Article |
|-------------------|--------------------------|----------------------|----------------|------------------------|------------------|-----------------|-----------------|-------------|-------------|
| l/min | m ³ /h | m | | m | rpm | A | | mm | |
| 18000 | 18 | 7 | 3 x 400V AC | 10 | 2815 | 1.6 | 1.1/2" [40] | 321 | GRU96010923 |
| 18000 | 18 | 7 | 3 x 400V AC | 10 | 2820 | 2 | 1.1/2" [40] | 410 | GRU96001718 |
| 18000 | 18 | 7 | 3 x 400V AC | 10 | 2815 | 1.6 | 1.1/2" [40] | 321 | GRU96001652 |
| 24012 | 24 | 2 | 1 x 230V AC | 5 | 2790 | 5.37 | 2" [50] | 455 | GRU96004586 |
| 24984 | 25 | 7 | 3 x 400V AC | 10 | 2820 | 2 | 2" [50] | 436 | GRU96010563 |
| | | | | | | | | | GRU96404179 |
| | | | | | | | | | GRU96468194 |
| | | | | | | | | | GRU96468356 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.