



## GRUNDFOS Submersible pump Series: SEG - Dompelpomp gietijzer met versnijdingswaaier - (0,9 - 2,6 kW)

### Characteristics

**Series:** SEG

**Connection:** Flange

**Pressure rating flange:** PN10

**Material pump casing:** Cast iron

**Material quality:** EN-JL1030

**Insulation class acc. to IEC:** F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m <sup>3</sup> /h	m		m	rpm	A		mm	
7992	8	10	3 x 400-415V AC	10	2750	3	DN40	546	GRU96075906
15012	15	10	1 x 230V AC	10	2890	6	DN40	546	GRU96075894
15984	16	10	3 x 400-415V AC	10	2860	3	DN40	546	GRU96075898
15984	16	10	3 x 400-415V AC	10	2860	3	DN40	546	GRU96075897
18000	18	10	1 x 230V AC	10	2820	8	DN40	546	GRU96075901
18000	18	10	3 x 400-415V AC	10	2900	7	DN40	652	GRU96075916
18000	18	10	3 x 400-415V AC	10	2750	3	DN40	546	GRU96075905
19008	19	10	3 x 400-415V AC	10	2830	8	DN40	652	GRU96075918
19008	19	10	3 x 400-415V AC	10	2700	4	DN40	546	GRU96075910
19008	19	10	3 x 400-415V AC	10	2870	6	DN40	614	GRU96075913
19008	19	10	3 x 400-415V AC	10	2700	4	DN40	546	GRU96075909
19008	19	10	3 x 400-415V AC	10	2870	6	DN40	614	GRU96075914
									GRU96878520
									GRU96878518
									GRU96878509
									GRU96878506
									GRU96878510
									GRU96878513
									GRU96878516

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.