



## GRUNDFOS Submersible pump Series: EF - Vuilwater pomp - gietijzer - 30 mm vrije doorgang

### Characteristics

**Series:** EF

**Connection:** Internal thread (BSPP)

**Material pump casing:** Cast iron

**Material quality:** EN-JL1030

**Insulation class acc. to IEC:** F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m <sup>3</sup> /h	m		m	rpm	A		mm	
32796	32.8	10	3 x 400-415V AC	10	2920	2.3	2" (50)	494	GRU96106551
39240	39.2	10	3 x 400-415V AC	10	2870	2.8	2" (50)	494	GRU96115116
44280	44.3	10	3 x 400-415V AC	10	2830	3.1	2" (50)	494	GRU96106559
44280	44.3	10	3 x 400-415V AC	10	2830	3.1	2" (50)	494	GRU96106558
46440	46.4	10	3 x 400-415V AC	10	2720	3.7	2" (50)	494	GRU96104196
									GRU96877510

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.