



## GRUNDFOS Submersible pump Series: DP -Vuilwater pomp - gietijzer - 30 mm vrije doorgang

### Characteristics

**Series:** DP

**Pressure rating flange:** PN10

**Material pump casing:** Cast iron

**Material quality:** EN-JL1030

**Insulation class acc. to IEC:** F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m <sup>3</sup> /h	m		m	rpm	A		mm	
42480	43	10	3 x 400-415V AC	10	2870	2.8	2" [50]	493	GRU96104204
46080	46	10	3 x 400-415V AC	10	2870	5.8	DN65	592	GRU96106542
48960	49	10	3 x 400-415V AC	10	2720	3.8	2" [50]	493	GRU96104209
48960	49	10	3 x 400-415V AC	10	2720	3.8	2" [50]	493	GRU96104208

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.