

ECON® Diaphragm drum pressure gauge Type 1481 bottom connection brass




Characteristics

Type: 1481
Accuracy class: 1.6 %
Pressure gauge attachment: Direct
Connection location: Below
Process connection: External thread
Cabinet material: Stainless steel 304

Characteristics [2]

Process connection material: Stainless steel 316
Material dial: Aluminium
Protection class: IP54
Medium temperature: -20 / 60 °C
Ambient temperature: -20 / 60 °C



Cabinet diameter	D	a	b	c	c1	c2	c3	G	G1	h	SW	Weight
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
63	64	10	47	5	2	13	13	85	3.7	53	14	0.23
100	101	20	55	6	3	20	19	132	4.8	87	22	0.5
160	161	15.5	51.5	6	3	20	19	196	5.8	115	22	0.9

Cabinet diameter	Measuring range	Pressure unit	Size process connection	Window material	Article
mm					
63	-100 / 0	mbar	1/4" BSPP[G]	Glass	685153
63	-20 / 40	mbar	1/4" BSPP[G]	Glass	685164
63	0 / 100	mbar	1/4" BSPP[G]	Glass	685114
100	0 / 60	mbar	1/2" BSPP[G]	Glass	10059949
100	0 / 100	mbar	1/2" BSPP[G]	Glass	10059950
100	0 / 160	mbar	1/2" BSPP[G]	Glass	10059951
100	0 / 250	mbar	1/2" BSPP[G]	Glass	10059952
100	0 / 400	mbar	1/2" BSPP[G]	Glass	684964

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.