




## ECON® Bourdon tube pressure gauge Type 331 rear connection brass

### Characteristics

- Type:** 331
- Model:** Bourdon tube pressure gauge
- Blow-out included:** No
- Pressure gauge attachment:** Direct
- Process connection:** External thread
- Process connection material:** Brass
- Protection class:** IP54
- Medium temperature:** -20 / 80 °C
- Ambient temperature:** -40 / 60 °C



Case diameter	D1	D2	b1	b2	e	sw	f	G
mm	mm	mm	mm	mm	mm	mm	mm	["]
80	83.5	80	32	62.5	5.5	22	-	G¼
100	101	99	49.5	83	17.5	22	30	G½
160	161	159	49,5*	83*	17.5	22	30	G½

\* @>

Cabinet diameter	Measuring range	Pressure unit	Accuracy class	Connection location	Size process connection	Cabinet material	Window material	Material dial	Maximum overpressure	Article
mm									bar	
80	0 / 10	bar	1.6 %	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Polycarbonate	Aluminium	13	EC003317G1B-4130
100	0 / 2.5	bar	1.0 %	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Glass	Aluminium	3	EC003311D2D1110
100	0 / 6	bar	1.0 %	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Glass	Aluminium	7.8	EC003311F2D1110
100	0 / 10	bar	1.0 %	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Glass	Aluminium	13	EC003311G2D1110
100	0 / 16	bar	1.0 %	Back eccentric	1/2" BSPP[G]	Stainless steel 304	Glass	Aluminium	32	EC003311H2D1110

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.