

## ECON® Paddleswitch fig. 8050 reedcontact with pipe segment

## **Characteristics**

Series: VXS **Type:** 8050

Sensor/feeler type: Paddel Model: Inline (with pipe piece)

Calibration: Water Sealing: NBR

Material switch housing: Plastic Contact version: Reedcontact SPST

**Switching power:** 230V AC / 1A / 26VA - 48V DC / 1A

Adjustable differential: No

## **Characteristics (2)**

Electrical connection: Plug EN 175301-803 type A

Level of protection (IP value): IP65

Max. pressure: 25 bar

Medium temperature: From -10 °C to 110 °C °C

Ambient temperature: -10 / 80 °C

Switch flow rate increasing	Switch flow rate decreasing	Maximum flow rate	Orifice	Process connection	Size process connection	Process connection material	Housing material	Paddle material	Article
l/min	l/min	I/min							
13.5 / 17	12 / 15.5	195	DN25	Internal thread (BSPP)	1" (25)	Brass	Brass	Brass	SKVXS25MMS-D
15.5 / 20.5	14.5 / 19	240	DN32	Internal thread (BSPP)	1.1/4" (32)	Brass	Brass	Brass	SKVXS32MMS- D

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



PR\_EC011194\_0008\_MVD\_EN\_05.05.2024