



GRUNDFOS Submersible pump Series: SE - Vuilwater pomp

Characteristics

Series: SE

Connection: Flange

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1040

Insulation class acc. to IEC: F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m ³ /h	m		m	rpm	A		mm	
69840	70	20	3 x 380-415V AC	10	2910	6.8	DN65	753	GRU96047517
69840	70	20	3 x 380-415V AC	10	2925	8.7	DN80	838	GRU96047997
74880	75	20	3 x 380-415V AC	10	2895	5.1	DN65	753	GRU96047509
123120	123	20	3 x 380-415V AC	10	1435	4.2	DN80	776	GRU96047533
183960	184	20	3 x 380-415V AC	10	1460	10	DN100	878	GRU96048069

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.