



GRUNDFOS Submersible pump Series: SEV

Characteristics

Series: SEV

Connection: Flange

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1040

Insulation class acc. to IEC: F

Discharge head	Nominal volume flow rate	Max. dimension of fixed parts	Maximum static pressure	Supply voltage	Motor power	Nominal current	Connection size	Pump diameter	Pump height	Article
m	m ³ /h	mm	bar		kW	A		mm	mm	
7.1	57.9	80	6	3 x 380-415V AC	1.5	2.8	DN80	409	798	GRU96047745
10.1	72	80	6	3 x 380-415V AC	2.1	4.2	DN80	409	798	GRU96047769
12.4	44.6	80	6	3 x 380-415V AC	2.9	6	DN80	409	798	GRU96047781
14.1	124.9	100	6	3 x 380-415V AC	4.9	10	DN100	457	889	GRU96047925
21.2	45	65	6	3 x 380-415V AC	3.8	6.8	DN65	396	771	GRU96047713
23.2	79.9	80	6	3 x 380-415V AC	4.8	8.7	DN80	456	874	GRU96047829
29.5	45	65	6	3 x 380-415V AC	4.8	8.7	DN65	456	848	GRU96047729

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.