

ECON® Ball valve Type: 7744 Stainless steel Internal thread (BSPP) 1000 PSI WOG



Characteristics

Type: 7744

Norm: EN (DIN)

Construction type: 2-way

Housing construction: 1-part

Housing material: Stainless steel

Material quality: 1.4408

Connection: Internal thread (BSPP)

Primary spindle seal material: PTFE

Tertiary spindle seal material: PTFE

Actuator material: 1.4301

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 205 °C

Application

- Light industrial applications up to 68 bar.

Technical Information

- Connection according to ISO 228-1 BSPP.
- Floating ball.
- Pressure class 1000 PSI WOG
- In sizes 1/4" - 2".

Construction


- One-piece housing construction.
- Reduced bore.

Options

- Connection in NPT according to ASME B1.20.1.

Size table:

DN	d	L	H	M	Weight
	mm	mm	mm	mm	kg
1/4" [8]	5	39	33	71	0.1
3/8" [10]	7	44	35	93	0.1
1/2" [15]	9.2	55	40	95	0.2
3/4" [20]	12.5	59	44	95	0.3
1" [25]	15	69	50	113	0.4
1.1/4" [32]	20	77	57	113	0.6
1.1/2" [40]	25	81	64	141	0.8
2" [50]	32	97	68	141	1.2



Pressure and temperature range

Size	Temperature range	-10	38	100	150	200	[°C]
1/4" - 2"	-10°C/+200°C	68	68	44	22	1	[bar]

Pressure class 1000 PSI WOG

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Article
1/4" [8]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC0774401/4-AABAG
3/8" [10]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC0774403/8-AABAG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Article
1/2" [15]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC0774401/2-AABAG
3/4" [20]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC0774403/4-AABAG
1" [25]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC077440001-AABAG
1.1/4" [32]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC0774411/4A-ABAG
1.1/2" [40]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC0774411/2A-ABAG
2" [50]	ISO 228-1	1000 PSI WOG	Manufacturer standard	Handle	Reduced bore	No	1.4408	PTFE	1.4401	EC077440002-AABAG

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.