


## ECON® Fire fighting valve Type: 2059 Bronze Straight Flange



### Characteristics

**Type:** 2059  
**Construction type:** Straight  
**Housing material:** Bronze  
**Material quality:** CC491K [RG5]  
**Surface protection:** Standard manufacturers coating  
**Connection:** Flange  
**Connection 2:** Storz coupling  
**Flange finish:** Flat face  
**Operation:** Hand wheel, non-rising with non-rising stem  
**Type of bonnet:** Flanged  
**Colour:** Red, RAL3000  
**Spindle material:** Chromium steel  
**Primary spindle seal material:** EPDM  
**Material bonnet:** CC491K [RG5]

**Bonnet gasket material:** EPDM

**Material storz coupling:** Brass

**Actuator material:** EN-JL1030

**Minimum medium temperature (continuous):** -10 °C

**Maximum medium temperature (continuous):** 80 °C

**Maximum pressure difference at 20 °C:** 10 bar

### Application

- Recommended in: Food & Beverages, Maritime, Utilities

DN	A	L	H1	M	Cam distance	Weight
mm	mm	mm	mm	mm	mm	[kg]
40	150	195	170	120	52	8,3
50	165	205	170	120	66	9,4
65	185	235	195	140	81	14

Pressure rating	Max. medium temperature
PN10	80°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.