



ECON® Fire fighting valve Type: 2058 Bronze Angle Pattern Flange

Characteristics

Type: 2058

Construction type: Angle Pattern

Housing material: Bronze

Material quality: CC491K [RG5]

Surface protection: Standard manufacturers coating

Connection: Flange

Connection 2: Storz coupling

Flange finish: Flat face

Operation: Hand wheel, non-rising with non-rising stem

Type of bonnet: Flanged

Colour: Red, RAL3000

Spindle material: Chromium steel

Primary spindle seal material: EPDM

Material bonnet: CC491K [RG5]

Bonnet gasket material: EPDM

Material storz coupling: Brass

Actuator material: EN-JL1030


Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 80 °C

Maximum pressure difference at 20 °C: 10 bar

Application

- Recommended in: Food & Beverages, Maritime, Utilities



DN	A	L1	H (open)	M	Cam distance	Weight
mm	mm	mm	mm	mm	mm	[kg]
40	150	140	190	120	52	7,3
50	165	150	190	120	66	8,4
65	185	165	220	140	81	11,6

Pressure rating	Max. medium temperature
PN10	80°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.